

# HVE-VELOCITY

HIGH AVAILABILITY DUAL ENCLOSURE SAN



HVE-VELOCITY

## FEATURES:

- High-availability storage server optimized for mission-critical storage applications
- Fully redundant, fault-tolerant system supporting hot swappable controller nodes and storage drives
- Two compute nodes and Active-Active configuration each supporting two Intel® Xeon Processors E5-2600 v3/v4 product family and up to 512GB of DDR4 memory
- 10GBE, PCIe NTB or SAS link between nodes for communication and fail-over
- Built-in LSI SAS3x36R SAS expander per node
- Intel® Trusted Platform Module (TPM) header to support Intel® Trusted Execution Technology (TXT)

## SOFTWARE DEFINED STORAGE

HVE-VELOCITY is powered by Open-E JovianDSS which is a high-performance ZFS file system designed especially for enterprise-sized software defined storage environments. With its unique features, the product ensures highest data reliability and integrity for optimal data storage, protection, and recovery. It addresses the needs of enterprise users seeking a unified NAS and SAN solution with thin provisioning, compression, and deduplication.

## FAULT-TOLERANCE STORAGE PLATFORM

HVE-VELOCITY platform is a 2U 24-SFF-Bay cluster-in-a-box solution that provides high-availability in an active-active configuration. This appliances is engineered with two Intel® S2600TP server boards (one board per node), each supporting dual Intel® Xeon® processors in the E5-2600 v4 product family. Both nodes process I/Os and provide simultaneous and balanced access to the logical devices, which significantly increases overall cluster performance. When failover occurs, the secondary node automatically takes over the devices, client connections, and all processes/services of the system. It provides protection from loss of revenue when access to data resources and critical business applications are disrupted. The HVE-VELOCITY platform eliminates SPOFs (single points of failure). The all 12G SAS SSD design allows faster access to data. It is optimized for mission-critical, enterprise-level storage applications.

## RECOVER YOUR DATA

Data protection prevents data loss and minimizes the recovery time with high-speed disaster recovery. The HVE-VELOCITY lowers the recovery point objective (RPO) and recovery time objective (RTO) in each backup strategy. It allows setting up an application backup with a retention interval as a disaster recovery plan for virtual environments based upon VMware. The software does not require the installation of any backup agent. With the HVE-VELOCITY, servers with crucial data can be easily and instantly restored in case of an unexpected disaster.

*open-e*



Tel: 866-958-6384 Fax: 866-203-0622 HVEConneXions.com

© 2017 HVE ConneXions All rights reserved

# SPECIFICATIONS:

## HVE-VELOCITY



<b>Dimensions:</b> (W x D x H) with chassis ears	mm : 482.6 x 815 x 88 inches: 19 x 32 x 3.5	<b>Front Panel:</b>	System power on
<b>Motherboard:</b> (per node)	Intel® Server Board S2600TP	<b>LEDs</b> (per node)	<b>A</b> <ul style="list-style-type: none"> <li>• Power (Secondary)</li> <li>• Warning</li> </ul> <b>B</b> <ul style="list-style-type: none"> <li>• Power (Primary)</li> <li>• Warning</li> </ul>
<b>Processor:</b> (per node)	<b>Support:</b> Intel® E5-2620 v3/v4 x 2 <b>QPI Speeds:</b> 9.6 GT/s, 8 GT/s, 7.2 GT/s <b>Socket Type:</b> Socket R3	<b>Drive Bays:</b>	<b>External:</b> 2.5" hot swap 24 <b>Internal:</b> 2.5" 2 (per node)
<b>Chipset Support:</b> (per node)	Intel C612 Chipset	<b>Expansion Slots:</b>	PCIe 3.0 5x8 (low profile)
<b>System Memory:</b> (Per node)	<ul style="list-style-type: none"> <li>• 16 DIMM slots in total across 8 memory channels</li> <li>• Registered DDR4 (RDIMM), Load Reduced DDR4 (LRDIMM)</li> <li>• Memory DDR4 transfer rates 1600/1866/2133</li> <li>• DIMM sizes of 4GB, 8GB, 16GB, or 32GB depending on ranks and technology</li> </ul>	<b>Internal I/O Connectors / Headers</b> (per node)	<ul style="list-style-type: none"> <li>• 1 x internal USB 2.0 connector (port 6/7)</li> <li>• 1 x 2x7 pin header for system fan module</li> <li>• 1 x 1x12 pin control panel header</li> <li>• 1 x DH-10 serial Port A connector</li> <li>• 1 x SATA 6GB/s port for SATA DOM</li> <li>• 4 x SATA 6GB/s connectors (port 0/1/2/3)</li> <li>• 1 x 2x4 pin header for Intel RMM4 Lite</li> <li>• 1 x 1x4 pin header for Storage Upgrade Ke</li> <li>• 1 x 1x8 pin backup power controller connector</li> <li>• 1 x SFF 8644</li> </ul>
<b>Bootable OS:</b>	16GB iSLC (Innodisk) SATADOM x 2	<b>Power Supply:</b>	1200W 1+1 redundant power supply
<b>HBA:</b>	9300-8i x 2+ 8643-8643 cable x 4	<b>Rear I/O</b>	1 x RJ45 IPMI port 2 x RJ45 1 x VGA 2 x USB 2.0 Type A 1 x Mini SAS HD
<b>Backplane:</b>	1 X 24-port 12GB SAS backplane	<b>Gross Weight:</b> (w/ PSU and rails)	41 kgs 90 lbs
<b>Expander Boards:</b>	2 x 36-port 12GB SAAS expander boards with 3 SFF-8643 connectors on each	<b>Expander Boards:</b>	2 x 36-port 12GB SAAS expander boards with 3 SFF-8643 connectors on each
<b>RAID Support:</b>	Intel RSTe SW RAID 0/1/10/5	<b>System Cooling:</b>	2 x 6056 fans
<b>Ethernet:</b>	X550-T2 x 2 for base model (SFP+ option available)	<b>Environmental Specifications:</b>	Temperature: 0°C- 35°C Humidity: 5%- 95% non-condensing
<b>Video:</b>	Integrated Matrox G200D2 Graphics Controller	<b>Mounting:</b>	Standard / 28" tool-less slide rails
<b>Server Management</b>	<ul style="list-style-type: none"> <li>• Onboard Server Engines LLC Pilot III</li> <li>• Supports Intel Remote Management Module 4 solutions</li> <li>• Intel Light-Guided Diagnostics on field units</li> <li>• Support for Intel SMS &amp; Intel IPNM (Need PMBus- compliant power supply)</li> </ul>		



Tel: 866-958-6384 Fax: 866-203-0622 HVEConneXions.com  
© 2017 HVE ConneXions All rights reserved

All specifications are subject to change without notice.

This document was created using the official VMware icon and diagram library. Copyright © 2017 VMware, Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws.

VMware does not endorse or make any representations about third party information included in this document, nor does the inclusion of any VMware icon or diagram in this document imply such an endorsement.